

# :Avalon N4

*High-quality Thermal Platesetting  
for 4-up and 6-up Printing*




:Avalon N4 brings today's commercial and packaging printers the high-quality digital plates they need to stay competitive. Whether you require the highly productive :Avalon N4-10 S or the cost-effective :Avalon N4-10 E, you are assured of a winning combination of exceptional imaging and rock-solid reliability. You can upgrade any time from the E model to the S model. Its streamlined operation and uncompromising image quality will allow you to handle more of even the most demanding jobs, with more profit.

Both models come with an optional inline punching system. The N4 L50, :N4 L100 and :N4 L300 plateloaders offer maximum convenience and automation.

MODELS	N4-10 E	N4-10 S
Platesetter Architecture		external drum
Laser technology		830 nm infrared thermal
Light source	16-channel infrared laser diode	32-channel infrared laser diodes
Image area	Maximum 830 mm x 633 mm (32.7" x 24.9") (Front margin 15 mm, rear margin 12 mm)	
Resolutions	2400 dpi	1200 – 2400 dpi
PLATE SIZES		
Maximum plate (lead edge x wrap)	830 mm x 660 mm (32.7" x 26")	
Minimum plate (lead edge x wrap)	324 mm x 370 mm standard - 304 mm x 370 mm optional (12.8" x 14.5") (12" x 14.5")	
Thickness	0.15 mm to 0.3 mm (6 to 12 mil)	
PLATES		
Approved Agfa Graphics plates	:Thermostar P970 / :Energy Elite / :Azura / :Azura TS :Amigo / :Ampio	

# :Avalon N4



## PLATEHANDLING CONFIGURATIONS

Plate loading	Manually With autoloader = automatic
Plate unloading	Manually
On-line processor (OLP)	Yes

## THROUGHPUT\*

724 x 615 mm (28.5" x 24.2")	11 pl/hr at 2,400 dpi	21 pl/hr at 2,400 dpi
---------------------------------	-----------------------	-----------------------

(\*)Throughput/Productivity may vary based on the sensitivity of the specific media used

## INTERNAL PUNCHING

Option	Online punch configurations for all major presses are available
--------	---

## PHYSICAL SPECIFICATIONS

Dimensions (W x D x H)	1,750 x 1,030 x 1,178 mm (68.9" x 40.6" x 46.4")
Main unit	
Approx Weight	645 kg (1,422 lbs.)
Power	Single Phase 200 V to 240 V +6%/-10%, 20A, 4.0 kW

## AUTOLOADERS

MODELS	N4 L50	N4 L100	N4 L300
Plate capacity	50	100	300
No. of cassettes	1	1	3
Slipsheet removal	No	Yes	Yes
Plate transport	Fully automatic loading	Fully automatic loading	Fully automatic loading
Power	Single phase 200V-240V +6% -10%, 5A, 1,0kW		
Weight	200 kg (440 lbs.)	340 kg (748 lbs)	765 kg (1,683 lbs)
Dimensions	1260 x 1335 x 1031mm (50" x 52.6" x 40.6")	1395 x 1775 x 1060 mm (55,0" x 69,9" x 41,7"	2590 x 1775 x 1060 mm (101,9" x 69,9" x 41,7")

## :Avalon N4 processor possibilities

:Elantrix 95 SX

:Azura C95